



M8 female panel mount connector ,90degree
Description:M8 female panel mount connector , PCB type





Assembly Instruction

Drilling schemes female insert (PCB):







Technical Data

Pin No.	3	4	4	5	6	8
Coding	А	А	D	В	A	A
Pin for reference	4 3 ○ ○ 1				$\begin{array}{c} 4\\ 3\\ \circ\\ \circ\\ \circ\\ 0\\ 2\\ \circ\\ 0\\ 1\end{array}$	$\begin{array}{c} 5 \\ 4 \\ \circ \\ 0 \\ 3 \\ \circ \\ 2 \\ 2 \\ 1 \end{array}$
Туре	panel mount					
Rated current	ЗA	3A	4A	3A	1.5A	1.5A
Rated voltage	60V	60V	60V	30V	30V	30V
Operating Temperature	-25 °C ~85 °C					
Degree of protection	IP67/IP68					
Connector locking system	PCB					
Mechanical operation	>500 mating cycles					
Contact resistance	≤10mΩ					
Material of connector	CuZn,PA					
Contact plating	Au(gold plating)					
Filling material	Epoxy resin					

Order Information



Remark:Contact us any time if you have custom requirements.

6

M12

M16

M18

M23

7/8"

Value

RJ45

USB

D-SUB

RD24

RD30