



M5

M8

M9

M16

M18

M23

7/8"

M12 male panel mount connector ,square.

Description:M12 male front panel mount connector , solder type





Assembly Instruction



Technical Data

Pin No.	3	4	5	8	12	17	5	4
Coding	А	А	А	A	А	A	В	D
Pin for reference		$2 \bigcirc 0 \bigcirc 1 \\ 3 \bigcirc 0 \bigcirc 4$			$\begin{array}{c} 2 \\ 0 \\ 3 \\ 4 \\ 5 \\ 6 \end{array} \begin{array}{c} 0 \\ 11 \\ 0 \\ 11 \\ 0 \\ 11 \\ 0 \\ 0 \\ 0 \\ $	$13 3 2 12 \\ 17 14 0 0 11 \\ 14 0 0 15 \\ 7 8 16 $		
Туре	panel mount							
Rated current	4A	4A	4A	2A	1.5A	1.5A	4A	4A
Rated voltage	250V	250V	60V	30V	30V	30V	60V	250V
Operating Temperature	-25°C~85°C							
Degree of protection	IP67/IP68							
Connector locking system	Solder							
Mechanical operation	>500 mating cycles							
Contact resistance	≤10mΩ							
Material of connector	CuZn,TPU							
Contact plating	Au(gold plating)							
Materail of housing	Brass/Zinc diecasting nickel plated							

Order Information Part No.



Remark:Contact us any time if you have custom requirements.

Value

RJ45

RD24

RD30

USB