



M9

M12

M18

M23

7/8"

Value

RJ45

M16 male panel mount connector ,straight.

Description:M16 male front panel mount connector , solder type





## Assembly Instruction







## **Technical Data**

| Pin No.                  | 2                             | 3(DIN) | 4    | 5    | 5(Stereo) | 6(DIN) | 7    |
|--------------------------|-------------------------------|--------|------|------|-----------|--------|------|
| Pin for reference        |                               |        |      |      |           |        |      |
| Туре                     | panel mount                   |        |      |      |           |        |      |
| Rated current            | 7A                            | 7A     | 6A   | 6A   | 6A        | 5A     | 5A   |
| Rated voltage            | 250V                          | 250V   | 250V | 250V | 250V      | 250V   | 125V |
| Operating Temperature    | -20°C~80 °C                   |        |      |      |           |        |      |
| Degree of protection     | IP67/IP68                     |        |      |      |           |        |      |
| Connector locking system | Solder                        |        |      |      |           |        |      |
| Mechanical operation     | >500 mating cycles            |        |      |      |           |        |      |
| Contact resistance       | ≤5mΩ                          |        |      |      |           |        |      |
| Material of connector    | CuZn,TPU                      |        |      |      |           |        |      |
| Contact plating          | Au(gold plating)              |        |      |      |           |        |      |
| Materail of housing      | Zinc diecasting nickel plated |        |      |      |           |        |      |

## **Order Information**



Remark:Contact us any time if you have custom requirements.