
D-SUB






- M16 female panel mount connector ,straight.
- Description:M16 female front panel mount connector, solder type






## **Assembly Instruction**



## Hole Size:



## **Technical Data**

Pin No.	2	3(DIN)	4	5	5(Stereo)	6(DIN)	7	
Pin for reference	Q 2	Φ <sup>2</sup> 0 3	20 0 3 0 0 1 4	40 0 5 0 1 3	20 0 <sub>4</sub> 0 0 <sub>5</sub>	20 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0	50 03 60 01	
Туре	panel mount							
Rated current	7A	7A	6A	6A	6A	5A	5A	
Rated voltage	250V	250V	250V	250V	250V	250V	125V	
Operating Temperature	-20°C~80°C							
Degree of protection	IP67/IP68							
Connector locking system	Solder							
Mechanical operation	>500 mating cycles							
Contact resistance	≤5mΩ							
Material of connector	CuZn,TPU							
Contact plating	Au(gold plating)							
Materail of housing	Zinc diecasting nickel plated							

## **Order Information**

Part No.	Model No.			
M16-PMS-FF-M18	RG163002			
Remark:Contact us any time if you have custom requirements.				