
M23 Series




- 623T rear panel mount female socket
- Description:623T rear panel mount square female socket, solder type





## **Assembly Instriction**





## **Technical Date**

Pin No.	6	9	12	16	19
Pin for reference		20 9 07 30 98 06 40 9 06	1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	10 10 10 10 10 10 10 10 10 10 10 10 10 1	20 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Coupling	Threaded coupling				
Rated current	20 A	8 x 8 A/1 x 20 A	8 A	8 A	16 x 8 A/3 x 10 A
Rated voltage	250 V	250 V	150 V	150 V	150 V
Operating Temperature	'-40℃~125℃				
Degree of protection	IP67				
Termination	Solder				
Mechanical operation	>500 mating cycles				
Contact resistance	≤3mΩ				
Material of contact	CuZn/CuSn(brass/bronze)				
Contact plating	Au(gold plating)				
Material of contact body	PET (UL 94 V-0)				
Material of housing	CuZn(brass,nickel plated)				
Wire gauge	2,5 mm²(AWG 14)	8x1,5 mm² (AWG 16)/ 1x2,5 mm² (AWG 14)	1,0 mm²(AWG 18)	1,0 mm²(AWG 18)	16x1 mm²(AWG 18)/ 3x1,5 mm² (AWG 16)

## **Order Information**

